



Sample image

C125-6

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Ring type terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui

Voltage (V)	AC / DC
690	AC

Rated impulse withstand voltage Uimp

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnector

Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
150	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

Conventional enclosed thermal current Ithe

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
150	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-20A	690	150
AC-21A	20 - 690	150
AC-22A	220 - 500	150
AC-22A	660 - 690	125

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-2	220 - 240	3	3	37
AC-2	380 - 440	3	3	55
AC-2	500 - 500	3	3	75
AC-2	660 - 690	3	3	55
AC-3	220 - 240	3	3	22
AC-3	380 - 440	3	3	37
AC-3	500 - 500	3	3	37
AC-3	660 - 690	3	3	30
AC-3	110 - 120	1	2	5,50
AC-3	220 - 240	1	2	11
AC-3	380 - 440	1	2	18,50
AC-4	220 - 240	3	3	10
AC-4	380 - 440	3	3	15
AC-4	500 - 500	3	3	15
AC-4	660 - 690	3	3	15
AC-4	110 - 120	1	2	2,20
AC-4	220 - 240	1	2	4
AC-4	380 - 440	1	2	7,50
AC-23A	220 - 240	3	3	37
AC-23A	380 - 440	3	3	75
AC-23A	500 - 500	3	3	90
AC-23A	660 - 690	3	3	55
AC-23A	110 - 120	1	2	11
AC-23A	220 - 240	1	2	22
AC-23A	380 - 440	1	2	37

Max Fuse Rating IEC		
Fuse characteristic	No. of Fuses	Current (A)
gG	1	200

UL60947-4-1 , UL508

Rated insulation voltage U_i	
	Voltage (V) AC / DC
	600 AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	150	0 - 40	–

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
	<i>tightening torque (Nm)</i>	<i>tightening torque (lb-in)</i>
	4,50	39,80

Rated short-time withstand current I_{sc}	
Time (s)	Current (A)
1	2000

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



GB/T14048.3



Power loss per pole	Power (W)
	3.80

Conditions during transport and storing			
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements	
-40	85	In case of temperatures below -5°C no shock load permissible	

Shock / Vibration	
Type of oscillation	Values
Resistance to shock	min. 5g, 30ms
Resistance to vibration	IEC 61373 (1999) Category 1, Class B

General Information

Text

- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature	
	Min. Temperature [°C]
	-25
	Max. Temperature [°C]
	60