



Sample image

KG161

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Bolt terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui						
			Voltage (V)	AC / DC		
			1000	AC		
Rated impulse withstand voltage Uimp						
Voltage (kV)		Overvoltage category	Pollution degree	Supply system		Function
8		III	3	Valid for lines with grounded common neutral termination		Switch / Switch disconnector
Rated uninterrupted current Iu/Ith						
Current (A)		Ambient temperature (°C)		Peak temperature (°C)	additional requirements	
160		50		55	Ambient temperature +50°C during 24 hours with peaks up to +55°C	
Conventional enclosed thermal current Ithe						
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements		No. of stages (from - to)	Mounting
160	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C		--	--
Rated operational current Ie						
Utilization category			Voltage (V)			Current (A)
AC-32A			20 - 400			160
AC-20A			1000			160
AC-21A			20 - 690			160
AC-22A			220 - 500			160
AC-22A			660 - 690			100
Rated operational power						
Utilization category		Voltage (V)		No. of phases	No. of poles	Power (kW)
AC-3		220 - 240		3	3	30
AC-3		380 - 440		3	3	45
AC-3		500 - 500		3	3	55
AC-3		660 - 690		3	3	37
AC-23A		220 - 240		3	3	30
AC-23A		380 - 440		3	3	55
AC-23A		500 - 500		3	3	75
AC-23A		660 - 690		3	3	37
Max Fuse Rating IEC						
Fuse characteristic			No. of Fuses			Current (A)
gG			1			160

UL60947-4-1, UL508

Rated insulation voltage Ui			
		Voltage (V)	AC / DC
		600	AC
Rated thermal current			
Current (A)		Ambient temperature (°C)	Additional Text
200		0 - 40	--

General Information

Text

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

CSA

Rated insulation voltage Ui			
		Voltage (V)	AC / DC
		600	AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	200	0 - 40	--

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
	tightening torque (Nm)	tightening torque (lb-in)
	14	125

Rated short-time withstand current I _{cw}		
	Time (s)	Current (A)
	1	3000

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

IEC 60947-6-1

IEC 60947-6-1
EN 60947-6-1

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Power loss per pole	
	Power (W)
	5

Conditions during transport and storing			
	Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
	-40	85	In case of temperatures below -5°C no shock load permissible

General Information	
Text	

- The wiring aid has to be removed before voltage is applied!
- EMC Note: This device is suitable for use in environment A and B.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.

Operating temperature		
	Min. Temperature [°C]	Max. Temperature [°C]
	-5	55



ring type terminal dimensions

A(mm)	20,00 mm
A(mm)	25,00 mm