



Sample image

KG210

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui						
			Voltage (V)	AC / DC		
			1000	AC		
Rated impulse withstand voltage Uimp						
Voltage (kV)		Overvoltage category	Pollution degree	Supply system		Function
8		III	3	Valid for lines with grounded common neutral termination		Switch / Switch disconnecter
Rated uninterrupted current Iu/Ith						
Current (A)		Ambient temperature (°C)		Peak temperature (°C)	additional requirements	
200		50		55	Ambient temperature +50°C during 24 hours with peaks up to +55°C	
Conventional enclosed thermal current Ithe						
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements		No. of stages (from - to)	Mounting size
200	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C		--	--
Rated operational current Ie						
Utilization category				Voltage (V)		Current (A)
AC-20A				1000		200
AC-21A				20 - 690		200
AC-22A				220 - 500		200
AC-22A				660 - 690		125
Rated operational power						
Utilization category			Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-3			220 - 240	3	3	37
AC-3			380 - 440	3	3	55
AC-3			500 - 500	3	3	75
AC-3			660 - 690	3	3	40
AC-23A			220 - 240	3	3	37
AC-23A			380 - 440	3	3	75
AC-23A			500 - 500	3	3	90
AC-23A			660 - 690	3	3	45
Max Fuse Rating IEC						
Fuse characteristic				No. of Fuses		Current (A)
gG				1		200

UL60947-4-1, UL508

Rated insulation voltage Ui			
		Voltage (V)	AC / DC
		600	AC
Rated thermal current			
		Current (A)	Ambient temperature (°C)
		200	0 - 40
Additional Text			
-			

General Information

Text

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

CSA

Rated insulation voltage Ui			
		Voltage (V)	AC / DC
		600	AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	200	0 - 40	--

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
	tightening torque (Nm)	tightening torque (lb-in)
	16	140

Rated short-time withstand current I _{sw}		
	Time (s)	Current (A)
	1	4000

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm²) or (AWG/kcmil)	Material of the wire
solid wire	Min.	1	16mm²	Copper
flexible wire	Max.	1	MCM 300	Copper
flexible wire	Max.	1	150mm²	Copper
flexible wire	Min.	1	25mm²	Copper
Single-core or stranded wire	Max.	1	185mm²	Copper
Single-core or stranded wire	Max.	1	MCM 350	Copper
flexible wire with sleeve	Max.	1	120mm²	Copper
flexible wire with ferrule according to DIN 46228	Min.	1	16mm²	Copper

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



Power loss per pole	
	Power (W)
	5

Conditions during transport and storing			
	Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
	-40	85	In case of temperatures below -5°C no shock load permissible

General Information	
Text	

- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- Use copper wire only. Do not coat the wire end with tin.
- Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.

Operating temperature		
	Min. Temperature [°C]	Max. Temperature [°C]
	-5	55