



C43

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

Sample image

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui						
		Voltage (V)	AC / DC			
		690	AC			
Rated impulse withstand voltage Uimp						
Voltage (kV)		Overvoltage category	Pollution degree	Supply system	Function	
6		III	3	Valid for lines with grounded common neutral termination		Switch / Switch disconnector
Rated uninterrupted current Iu/Ith						
Current (A)		Ambient temperature (°C)		Peak temperature (°C)	additional requirements	
63		55		60	Ambient temperature +55°C during 24 hours with peaks up to +60°C	
Conventional enclosed thermal current Ithe						
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
63	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--
Rated operational current Ie						
Utilization category			Voltage (V)	Current (A)		
AC-15			220 - 240	16		
AC-15			380 - 440	7		
AC-20A			690	63		
AC-21A			20 - 690	63		
AC-22A			220 - 500	63		
AC-22A			660 - 690	63		
Rated operational power						
Utilization category		Voltage (V)	No. of phases	No. of poles	Power (kW)	
AC-2		220 - 240	3	3	18,50	
AC-2		380 - 440	3	3	30	
AC-2		500 - 500	3	3	40	
AC-2		660 - 690	3	3	37	
AC-3		220 - 240	3	3	11	
AC-3		380 - 440	3	3	18,50	
AC-3		500 - 500	3	3	18,50	
AC-3		660 - 690	3	3	18,50	
AC-3		110 - 120	1	2	3	
AC-3		220 - 240	1	2	6	
AC-3		380 - 440	1	2	11	
AC-4		220 - 240	3	3	5,50	
AC-4		380 - 440	3	3	7,50	
AC-4		500 - 500	3	3	7,50	
AC-4		660 - 690	3	3	7,50	
AC-4		110 - 120	1	2	1,20	
AC-4		220 - 240	1	2	2,40	
AC-4		380 - 440	1	2	4	
AC-23A		220 - 240	3	3	15	
AC-23A		380 - 440	3	3	30	
AC-23A		500 - 500	3	3	45	
AC-23A		660 - 690	3	3	40	

Rated operational power				
Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-23A	110 - 120	1	2	4
AC-23A	220 - 240	1	2	10
AC-23A	380 - 440	1	2	18,50

Max Fuse Rating IEC		
Fuse characteristic	No. of Fuses	Current (A)
gG	1	80

UL60947-4-1, UL508

Rated insulation voltage Ui		
Voltage (V)	AC / DC	
600	AC	

Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
65	0 - 40	--	

CSA

Rated insulation voltage Ui		
Voltage (V)	AC / DC	
600	AC	

Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
65	0 - 40	--	

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
tightening torque (Nm)	tightening torque (lb-in)	
3	26,40	

Rated short-time withstand current Icw		
Time (s)	Current (A)	
1	1000	

Size of conductor					
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm²) or (AWG/kcmil)	Material of the wire	
solid wire	Min.	1	1.5mm²	Copper	
solid wire	Min.	2	1.5mm²	Copper	
flexible wire	Min.	1	4mm²	Copper	
flexible wire	Max.	2	AWG 6	Copper	
flexible wire	Min.	2	4mm²	Copper	
flexible wire	Max.	2	10mm²	Copper	
Single-core or stranded wire	Max.	2	AWG 6	Copper	
Single-core or stranded wire	Max.	2	16mm²	Copper	
flexible wire with ferrule according to DIN 46228	Min.	1	2.5mm²	Copper	
flexible wire with ferrule according to DIN 46228	Min.	2	2.5mm²	Copper	
flexible wire with ferrule according to DIN 46228	Max.	2	10mm²	Copper	

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Power loss per pole		
		Power (W)
		1,70
Conditions during transport and storing		
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible
Shock / Vibration		
Type of oscillation	Values	
Resistance to shock	min. 5g, 30ms	
Resistance to vibration	IEC 61373 (1999) Category 1, Class B	
General Information		
Text		
- Do not lubricate or treat contacts. - Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology. - Use copper wire only. Do not coat the wire end with tin. - Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications. - Use only fully insulated cable lugs resp. FASTON receptacles. - After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.		
Operating temperature		
Min. Temperature [°C]		Max. Temperature [°C]
-25		60