



C26

Type Size: S1

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

Sample image

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage U_i

Voltage (V)	AC / DC
690	AC

Rated impulse withstand voltage U_{imp}

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	switch

Rated uninterrupted current I_u /lth

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
32	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

Conventional enclosed thermal current I_{the}

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
32	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

Rated operational current I_e

Utilization category	Voltage (V)	Current (A)
AC-15	220 - 240	14
AC-15	380 - 440	6
AC-20A	690	32
AC-21A	20 - 690	32
AC-22A	220 - 500	32
AC-22A	660 - 690	32

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-2	220 - 240	3	3	8
AC-2	380 - 440	3	3	15
AC-2	500 - 500	3	3	18,50
AC-2	660 - 690	3	3	15
AC-3	220 - 240	3	3	5,50
AC-3	380 - 440	3	3	11
AC-3	500 - 500	3	3	11
AC-3	660 - 690	3	3	11
AC-3	110 - 120	1	2	2,20
AC-3	220 - 240	1	2	4
AC-3	380 - 440	1	2	5,50
AC-4	220 - 240	3	3	2,70
AC-4	380 - 440	3	3	5,50
AC-4	500 - 500	3	3	5,50
AC-4	660 - 690	3	3	5,50
AC-4	110 - 120	1	2	0,75
AC-4	220 - 240	1	2	1,50
AC-4	380 - 440	1	2	3
AC-23A	220 - 240	3	3	7,50
AC-23A	380 - 440	3	3	15
AC-23A	500 - 500	3	3	15
AC-23A	660 - 690	3	3	15
AC-23A	110 - 120	1	2	2,20

Rated operational power				
Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-23A	220 - 240	1	2	4
AC-23A	380 - 440	1	2	7,50
Max Fuse Rating IEC				
Fuse characteristic	No. of Fuses			Current (A)
gG	1			50

UL60947-4-1 , UL508

Rated insulation voltage Ui			
		Voltage (V)	AC / DC
		600	AC
Rated thermal current			
		Current (A)	Ambient temperature (°C) Additional Text
		40	0 - 40 --

CSA

Rated insulation voltage Ui			
		Voltage (V)	AC / DC
		600	AC
Rated thermal current			
		Current (A)	Ambient temperature (°C) Additional Text
		40	0 - 40 --

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
		tightening torque (Nm)
		1,30
		tightening torque (lb-in)
		12

Rated short-time withstand current Icw		
		Time (s)
		1
		Current (A)
		350

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm²) or (AWG/kcmil)	Material of the wire
solid wire	Min.	1	1mm²	Copper
solid wire	Min.	2	1mm²	Copper
flexible wire	Min.	1	1.5mm²	Copper
flexible wire	Max.	2	6mm²	Copper
flexible wire	Max.	2	AWG 10	Copper
flexible wire	Min.	2	1.5mm²	Copper
Single-core or stranded wire	Max.	2	6mm²	Copper
Single-core or stranded wire	Max.	2	AWG 8	Copper
flexible wire with ferrule according to DIN 46228	Min.	1	1mm²	Copper
flexible wire with ferrule according to DIN 46228	Max.	2	4mm²	Copper
flexible wire with ferrule according to DIN 46228	Min.	2	1mm²	Copper

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Power loss per pole		
		Power (W)
		1,30
Conditions during transport and storing		
	Minimum temperature (°C)	Maximum temperature (°C)
	-40	85
	additional requirements	
	In case of temperatures below -5°C no shock load permissible	
Shock / Vibration		
Type of oscillation	Values	
Resistance to vibration	Min. 4g, 2-100Hz, 1,6mm	
Resistance to shock	Min. 5g, 6ms	
Resistance to vibration	IEC 61373 (1999) Category 1, Class B	
General Information		
Text		
- Do not lubricate or treat contacts. - Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology. - Use copper wire only. Do not coat the wire end with tin. - Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications. - Use only fully insulated cable lugs resp. FASTON receptacles. - After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.		
Operating temperature		
	Min. Temperature [°C]	Max. Temperature [°C]
	-25	60